

# Efficiency

- Advanced MPPT technology with up to 99.9% efficiency
- Up to 22A PV input current for high power PV module

## Safety

- 360 degrees of security from hardware to software
- IEC safety approvals

## All in one

• Up to 100A charging current

### Reliable

- Outputs high quality pure sine wave AC power
- Up to 6 units in parallel connection

# **User-Friendly**

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

# Intelligent

- Exclusive Li-ion battery BMS dual activation
- Time-slot function to save cost with peak-valley















MODEL	SYP 5K-U	CAN BE
INVERTER OUTPUT	on ax o	SET
Rated Output Power	5,000W	
Max.Peak Power	10,000VA	
Rated Output Voltage	120Vac (L/N/PE single-phase)	
Load Capacity of Motors	4HP	v
Rated AC Frequency	50/60Hz	_/
Waveform	Pure sine wave	V
Switch Time	10ms (typical)	
Parallel Capacity	1-6 units (single/split/three phase)	
BATTERY		
Battery Type	Li-ion / Lead-acid / User-define	
Rated Battery Voltage	48Vdc	V
Voltage Range	40~60Vdc	
Max.MPPT Charging Current	100A	
Max.Mains/Generator Charging Current	40A	
Max.Hybrid Charging Current	100A	
PV INPUT	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	V
Num. of MPPT	1	
Max.PV array power	5,500W	
Max.input current	22A	
Max.Voltage of Open Circuit	500Vdc	
MPPT Voltage Range	120~450Vdc	
MAINS / GENERATOR INPUT		
Input Voltage Range	90~140Vac	
Frequency Range	50/60Hz	-
Bypass Overload Current	63A	
EFFICIENCY		
MPPT Tracking Efficiency	99.9%	
Max. Battery Inverter Efficiency	92%	
GENERAL		
Dimensions	446.9*350*133mm (1.47*1.15*0.44ft)	
Weight	14kg (30.86lb)	
Protection Degree	IP20, indoor only	
Operating Temperature Range	-10~55℃	
Noise	≤60dB	
Cooling Method	Forced air cooling with adjustable air speed	
Warranty	18 months	
COMMUNICATION		
Embedded Interfaces	RS485 / USB / Dry contact	<b></b>
External Modules (Optional)	Wi-Fi / GPRS	<b>✓</b>
CERTIFICATION		
Safety	CE(IEC 62109-1/2)	
EMC	EN61000	
RoHS	Yes	